PLAYGROUND FLOORING

SAFEPOL MULTICOLOR WITH TPV GRANULES

Elastic, safety wet-pour flooring ideal for children playgroundflooring, applied at site in various thickness from 4cm up to 20cm, even on compacted, clean, dry gravel and on cement or asphalt surfaces.

Consists of a mixture of **PU BINDER 1118** and **RECYCLED RUBBER 858** in granulometry of 1-3mm for the first layer (**SAFEPOL**) and of a mixture of **PU BINDER 1118** and **KDF TPV** granules in granulometry of 1-3mm or 2-4mm for the upper layer (**SAFEPOL TPV MULTICOLOR**). The final top coating over the TPV surface is the UV-resistant, mat, top coating **POLYSPORT XP 1069** in two crossing layers.

It can create many designs and patterns in a variety of **KDF TPV** colors.



Steps:


- 1. PU PRIMER 870 Special, polyurethane primer. Applied by airless sprayer or brush.
- 2. Mixture of PU BINDER 1118 and RECYCLED RUBBER 858 in granulometry of 1-3mm.

Applied by flat metal trowel after spreading and leveling with rake and straightedge. Rolling with cylinder follows for compacting.

- 3. Mixture of PU BINDER 1118 and KDF TPV granules in granulometry of 1-3mm or 2-4mm.
 - Applied by flat metal trowel after spreading and leveling with rake and straightedge. Rolling with cylinder follows for compacting.
- 4.POLYSPORT XP 1069 UV-resistant, two-component, universal, mat, top coating for the protection of EPDM and TPV granules against UV radiation.

Applied in two crossing layers by airless sprayer or short haired mohair roller on the surface in the desired color, as dual protection from UV sunlight and color fading while giving the possibility to crate different designs and patterns. Necessary protection for all EPDM/TPV colors except basic colors of KDF's colorchart, E3 & E10 and TPV 6 & TPV 9.





Description	Consumption
PU PRIMER 870 - Special, polyurethane, primer.	0.2-0.3kg/m ² for 2 layers
PU BINDER 1118 - Polyurethane binder.	1kg/m ² for 10mm mixture
RECYCLED RUBBER 858 - SBR granules in granulometry of 1-3mm.	6kg/m² for 10mm mixture
PU BINDER 1118 - Polyurethane binder.	2kg/m² for 10mm mixture
KDF TPV granules in granulometry of 1-3mm or 2-4mm.	10kg/m² for 10mm mixture
POLYSPORT XP 1069 - UV-resistant, two-component, universal, mat, top coating for the protection of EPDM/TPV granules against UV radiation.	0.4kg/m ² for 2 layers