## **OUTDOOR SPORTS FLOORING**

## **WET-POUR POLYFLEX AEL-EX**

Outdoor highly flexible, acrylic system, ideal for tennis, basketball, volleyball, handball, football, multipurpose courts, as well as any other outdoor sports court.


Combination of a mixture of **PU BINDER 1118** plus **RECYCLED RUBBER 858,** in granulometry of 0.5-2mm, and acrylic coatings in total thickness of 8mm up to 14mm.



## Steps:

- 1.PU PRIMER 870 Special, polyurethane primer.
  - Applied by airless sprayer or brush on asphalt surfaces or on waterproof concrete surfaces, without rising humidity issues.
- 2. Mixture of PU BINDER 1118 and RECYCLED RUBBER 858(minimum 6mm) Elastic, shock-absorbent, wetpour system.
  - The **RECYCLED RUBBER 858** is in granulometry of 0.5-2mm. The mixture is applied by paving machine in thickness of 6mm to 12mm or more.
- 3. **ELASTOTURF 851 Acrylic, elastic, slip-resistant coating for sports flooring systems.**

Consists of acrylic resins, quartz sand and special improver. Creates multi-purpose sports flooring systems. Highly resistant to adverse weather conditions (snow, frost, heat waves etc.) after drying. Applied by squeegee in 2 layers at least.



Description	Consumption
PU PRIMER 870 - Special, polyurethane, prime.	0.2-0.3kg/m <sup>2</sup> for 2 layers
PU BINDER 1118 - Polyurethane binder.	1.32kg/m² for 10mm mixture
RECYCLED RUBBER 858 - SBR granules in granulometry of 0.5-2mm.	6kg/m² for 10mm mixture
ELASTOTURF 851 - Acrylic, elastic, slip-resistant, coating for sports flooring systems.	3.5-3.8kg/m <sup>2</sup> for 3 layers