

must be used within 20-30 minutes of mixing at 25°C. The surface must be dry and clean.

- Material coverage lies between 1.3 - 2.5 Kg/m² and the material consumption depends on the surface structure (grain size, compaction, evenness) and on the temperature of substrate, ambience and material. Substrate temperatures must not exceed 50°C as this would liquefy the material.
- During the first hours after application, the coating had to be protected from direct contact with water as this could cause foaming of the material. In case of (expected) rain, **POLAPLAST P22** should not be applied.
- Pore-sealed surface with **POLAPLAST P22** track material can be recoated during the first 48 hours after application without the use of primer if the surface is dry and clean.

CONSUMPTION

1.3 - 2.5 kg/m², depends on the porosity of the substrate.

APPLICATION TOOLS

Flat trowel.



PACKAGING

Supplied in barrels and drums(set).



REMARKS

Use a slow rotating mixer at approximately 300-500rev/min for at least 3-4 minutes until the blend is homogenous and streak free. Ensure that the mixer reaches the side and bottom area of and mix it again for one additional minute.

CAUTION

The application must take place in well-aired places using protective gloves. Skin or eye contact must be avoided, otherwise wash carefully with soap and water.

KDF - Kataskeves Dapedon LTD
e : exports@kdf.gr w : www.kdf.gr

Showroom Office
1 Papanikolaou Ave, Pefka
57010, Thessaloniki, Greece
t / f : 0030 2310 829598

Accounting Office
19 Mitropoleos Str
54624, Thessaloniki, Greece



KDF

Sports Flooring Systems & Building Materials

50 YEARS OF EXPERIENCE

For more information consult the safety data sheet.

The information given here is true, represents our best knowledge and is based not only on laboratory work, but also on field experience. However, because of numerous factors affecting results we offer this information without any guarantee and no patent liability is assumed. For additional information or questions, contact the technical department of KDF LTD.

KDF - Kataskeves Dapedon LTD
e : exports@kdf.gr w : www.kdf.gr

Showroom Office
1 Papanikolaou Ave, Pefka
57010, Thessaloniki, Greece
t / f : 0030 2310 829598

Accounting Office
19 Mitropoleos Str
54624, Thessaloniki, Greece

